XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

XSVI-6522
INSTALLATION INSTRUCTIONS

In the Dodge and Jeep vehicles listed below there are no 12 volt accessory wires currently in the factory harness making the installer run an accessory wire to the fuse box or underneath the steering column when installing an aftermarket radio. The XSVI-6522 is designed to provide a 12 volt 10 amp switched accessory output along with the rest of the wires needed to install an aftermarket radio. The R.A.P. (Retained Accessory Power) function, where power is supplied to the radio after the ignition is shut off until one of the front doors are opened, is retained by the XSVI-6522.

NOTE: ***The XSVI-6522 does not retain use of the factory amplifier if so equipped.*** **INITIALIZE THE XSVI INTERFACE BEFORE TURNING ON RADIO: With all connections made and harnesses connected to the vehicle, turn ignition key to the ON position for thirty seconds, then turn key off.**

Wiring the XSVI-6522: Wiring up the XSVI-6522 is like wiring up any other wire harness that would attach to the aftermarket radios harness.The Metra/EIA wire code can be found on the back of this package that will aid you in the wiring of your aftermarket radio.

(See Applications on back of page)

INSTXSVI-6522 **Rev. 03/12/10**
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2010

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007

APPLICATIONS

CHRYSLER
300 2008-2010
ASPEN 2008-2009
SEBRING 2007-2010
TOWN & COUNTRY 2008-2010

DODGE
AVENGER 2008-2010
CHALLENGER 2009-2010
CHARGER 2008-2010
DAKOTA 2008-2009
DURANGO 2008-2009
GRAND CARAVAN 2008
JOURNEY 2009-2010
MAGNUM 2008
NITRO 2007-2010
RAM 1500 2009-2010
RAM 2500/3500 2010

JEEP
COMMANDER 2008-2009
COMPASS 2009
GRAND CHEROKEE 2008-2010
LIBERTY 2008-2010
PATRIOT 2009-2010
WRANGLER 2007-2010

Rev. 10/01/07 INSTXSVI-6522
1-800-221-0932 www.metraonline.com
METRA ELECTRONICS CORPORATION
© COPYRIGHT 2007